

Size	Model No	Voltage	Capacity	Dimension with tube		Standard Charge		Rapid Charge		Weight Approx
		(V)	(mAh)	Diameter	Height	Current	Time	Current	Time	(g)
				(mm)	(mm)	(mA)	(h)	(mA)	(h)	
C	D-C1500A	1.2	1500	26	50.0	150	15	1500	1.2	56
C	D-C2000A	1.2	2000	26	50.5	200	15	2000	1.2	65
C	D-C2000B	1.2	2000	25	50.0	200	15	2000	1.2	65
C	D-C2500H	1.2	2500	25.8	50.0	250	15			70
D	D-1/2D2200	1.2	2200	33	36.5	220	15	2200	1.2	70
D	D-1/2D2200H	1.2	2200	33	36.5	220	15			75
D	D-D1200A	1.2	1200	33	61.5	120	15	1200	1.2	66
D	D-D1500A	1.2	1500	33	61.5	150	15	1500	1.2	66
D	D-D4000A	1.2	4000	33	61.5	400	15	4000	1.2	135
D	D-D4000B	1.2	4000	33	60.5	400	15	4000	1.2	135
D	D-D4000H	1.2	4000	33	60.5	400	15			135
D	D-D4500A	1.2	4500	33	61.5	450	15	4500	1.2	138
D	D-D4500B	1.2	4500	33	60.5	450	15	4500	1.2	138
D	D-D4500H	1.2	4500	33	60.5	450	15			138
D	D-D5000A	1.2	5000	33	61.5	500	15	5000	1.2	140
D	D-D5000B	1.2	5000	33	60.5	500	15	5000	1.2	140
D	D-3/2D7000	1.2	7000	33	90.5	700	15	3500	2.5	195
D	D-3/2D7000H	1.2	7000	33	90.5	700	15			195
SC	D-SC1500P	1.2	1500	23	43.0	150	15	1500	1.2	49
SC	D-SC1700H	1.2	1700	23	43.0	170	15	0	0	49
C	D-C2000H	1.2	2000	25.8	50.0	200	15	0	0	65
C	D-C2500A	1.2	2500	26	50.5	250	15	2500	1.2	70
C	D-C2500B	1.2	2500	25.8	50.5	250	15	2500	1.2	70
AA	D-AA1100A	1.2	1100	14.5	50.5	110	15	1100	1.2	25
AA	D-AA1100B	1.2	1100	14.5	49.0	110	15	1100	1.2	25
AA	D-4/3AA1300	1.2	1300	14.5	65.5	130	15	1300	1.2	32
A	D-4/3A2000	1.2	2000	17	67.0	200	15	2000	1.2	44
SC	D-SC2300P	1.2	2300	23	43.0	230	15	2300	1.2	54
SC	D-4/5SC1200PQ	1.2	1200	23	34.0	120	15	1200	1.2	40
SC	D-4/5SC1400PQ	1.2	1400	23	34.0	140	15	1400	1.2	41
SC	D-SC1300PQ	1.2	1300	23	43.0	130	15	1300	1.2	49
SC	D-SC1500PQ	1.2	1500	23	43.0	150	15	1500	1.2	49
SC	D-SC1700PQ	1.2	1700	23	43.0	170	15	0	0	49
SC	D-SC1900PQ	1.2	1900	23	43.0	190	15	1900	1.2	50
SC	D-SC2100PQ	1.2	2100	23	43.0	210	15	2100	1.2	50
SC	D-SC2300PQ	1.2	2300	23	43.0	230	15	2300	1.2	54
SC	D-4/3SC2200PQ	1.2	2200	23	50.0	220	15	2200	1.2	60

NOTE: A-High cap; B-Low cap; P-High rate discharge; H-High temperature.

***-New products; **-Discharge at 0.2C after charging at 0.1C for 15 hours.**

#-WidthiÁThicknessiÁHeight.